

KBR:dcf 7/18/06 540427 305264.02  
PATENT

Attorney Reference Number 3382-69905-01  
Application Number 10/697,502

### Claims

1. – 33. (canceled)

34. (currently amended) In a receiver, a method comprising:  
detecting a descriptor within data transmitted by a transmitter;  
selecting between conventional and robust channels, wherein relative to data of the conventional channel, data of the robust channel have a higher level of robustness to transmission errors due to an increase of redundancy in the data of the robust channel;  
obtaining rate information and identifying a corresponding set of buffer parameters from the descriptor;  
configuring memory resources and flow control logic to provide elementary stream acquisition according to guidelines embodied by the identified set of buffer parameters; and  
buffering the data of the selected channel until a buffer contains more than an initial buffer fullness value of the data of the selected channel.

35. (previously presented) The method of claim 34, further comprising reconfiguring the memory resources and the flow control logic upon receipt of a new descriptor.

36. – 38. (canceled)

39. (currently amended) A receiver, comprising:  
means for detecting a descriptor within transmitted data;  
means for deciding which of conventional and robust channels to select, wherein relative to data of the conventional channel, data of the robust channel have a higher level of robustness to transmission errors due to an increase of redundancy in the data of the robust channel;  
means for determining a rate and for identifying a corresponding set of buffer parameters from the descriptor;  
means for configuring memory resources and flow control logic to provide elementary stream acquisition according to guidelines embodied by the identified set of buffer parameters; and  
means for decoding the data of the selected channel when a buffer contains greater than an

KBR:der 7/18/06 540427 305264.02  
PATENT

Attorney Reference Number 3382-69905-01  
Application Number 10/697,502

initial buffer fullness value of the data of the selected channel.

40. (previously presented) The receiver of claim 39, wherein the means for configuring memory resources and flow control logic reconfigures the buffer upon receipt of a new descriptor.

41. (canceled)

42. (canceled)

43. (previously presented) The method of claim 34, further comprising monitoring reception characteristics and statistics for use in the selecting.

44. (previously presented) The method of claim 43, wherein the monitoring includes monitoring symbol rate for the conventional channel and symbol rate for the robust channel.

45. (previously presented) The method of claim 43, wherein the monitoring includes monitoring one or more of signal-to-noise ratio, carrier-to-noise ratio, average signal energy, and peak signal energy of the transmitted data, and wherein the transmitted data includes the data of the conventional channel and the data of the robust channel.

46. (previously presented) The method of claim 43, wherein the monitoring includes monitoring extent of packet corruption.

47. (previously presented) The method of claim 34, wherein the conventional channel is a first portion of a transmission channel and the robust channel is a second portion of the transmission channel.

48. (currently amended) The method of claim 47, wherein the descriptor includes multiple sets of buffer parameters, and wherein the multiple sets address transmission with different degrees of robustness to transmission errors such that rate for the conventional channel and rate for the robust

KBR:dcv 7/18/06 540427 305264.02  
PATENT

Attorney Reference Number 3382-69905-01  
Application Number 10/697,502

channel vary from set to set at a ~~given fixed rate for the transmission channel.~~

49. (currently amended) The method of claim 47, wherein rate for the transmission channel exceeds rate for the conventional channel plus and exceeds rate for the robust channel ~~by an amount that varies depending on transmission robustness.~~

50. (previously presented) The method of claim 34, wherein the relatively higher level of robustness of the data of the robust channel is in terms of increased redundancy through channel coding techniques for the data of the robust channel.

51. (currently amended) The method of claim 34, wherein the relatively higher level of robustness of the data of the robust channel is in terms of increased use of cyclical redundancy codes or convolutional ~~block~~ codes within the data of the robust channel.

52. (previously presented) A computer-readable medium storing computer-executable instructions for causing the receiver programmed thereby to perform the method of claim 34.

53. (previously presented) The receiver of claim 39, wherein the means for deciding includes means for monitoring reception characteristics and statistics for use in the deciding.

54. (previously presented) The receiver of claim 53, wherein the monitoring includes monitoring symbol rate for the conventional channel and symbol rate for the robust channel.

55. (previously presented) The receiver of claim 53, wherein the monitoring includes monitoring one or more of signal-to-noise ratio, carrier-to-noise ratio, average signal energy, and peak signal energy of the transmitted data, and wherein the transmitted data includes the data of the conventional channel and the data of the robust channel.

56. (previously presented) The receiver of claim 53, wherein the monitoring includes monitoring extent of packet corruption.

KBR:dcv 7/18/06 540427 305264.02  
PATENT

Attorney Reference Number 3382-69905-01  
Application Number 10/697,502

57. (previously presented) The receiver of claim 39, wherein the conventional channel is a first portion of a transmission channel and the robust channel is a second portion of the transmission channel.

58. (currently amended) The receiver of claim 57, wherein the descriptor includes multiple sets of buffer parameters, and wherein the multiple sets address transmission with different degrees of robustness to transmission errors such that rate for the conventional channel and rate for the robust channel vary from set to set ~~at a given fixed rate for the transmission channel.~~

59. (currently amended) The receiver of claim 57, wherein rate for the transmission channel exceeds rate for the conventional channel ~~plus and exceeds~~ rate for the robust channel ~~by an amount that varies depending on transmission robustness.~~

60. (previously presented) The receiver of claim 39, wherein the relatively higher level of robustness of the data of the robust channel is in terms of increased redundancy through channel coding techniques for the data of the robust channel.

61. (currently amended) The receiver of claim 39, wherein the relatively higher level of robustness of the data of the robust channel is in terms of increased use of cyclical redundancy codes or convolutional ~~block~~ codes within the data of the robust channel.

62. (currently amended) In a receiver, a method comprising:  
obtaining information for multiple buffer models;  
in the receiver, selecting between a conventional channel and a robust channel, wherein relative to data of the conventional channel, data of the robust channel have a higher level of robustness to transmissions errors due to an increase of redundancy in the data of the robust channel;  
based at least in part upon rate of the data of the selected channel, identifying in the receiver a buffer size parameter from among multiple buffer size parameters of the multiple buffer models;  
configuring a buffer in the receiver according to the identified buffer size parameter; and

KBR:der 7/18/06 540427 305264.02  
PATENT

Attorney Reference Number 3382-69905-01  
Application Number 10/697,502

in the buffer, buffering the data from the selected channel.

63. (previously presented) The method of claim 62, wherein the selecting is based at least in part upon monitoring symbol rate for the conventional channel and symbol rate for the robust channel.

64. (previously presented) The method of claim 62, wherein the selecting is based at least in part upon monitoring one or more of signal-to-noise ratio, carrier-to-noise ratio, average signal energy, and peak signal energy of a transmitted signal including the data of the conventional channel and the data of the robust channel.

65. (previously presented) The method of claim 62, wherein the selecting is based at least in part upon monitoring of extent packet corruption.

66. (previously presented) The method of claim 62, wherein the multiple buffer models are applicable to both the conventional channel and the robust channel.

67. (previously presented) The method of claim 62, wherein the data includes packets for a video stream.

68. (previously presented) The method of claim 62, wherein the identifying the buffer size parameter includes selecting the buffer size parameter from one of the multiple buffer models.

69. (previously presented) The method of claim 62, wherein the identifying the buffer size parameter includes interpolating between plural buffer size parameters of plural of the multiple buffer models.

70. (previously presented) The method of claim 62, wherein the conventional channel is a first portion of a transmission channel and the robust channel is a second portion of the transmission channel.

KBR:der 7/18/06 540427 305264.02  
PATENT

Attorney Reference Number 3382-69905-01  
Application Number 10/697,502

71. (currently amended) The method of claim 70, wherein the multiple buffer models address transmission with different degrees of robustness to transmission errors such that rate for the conventional channel and rate for the robust channel vary from buffer model to buffer model ~~at a given fixed rate for the transmission channel.~~

72. (currently amended) The method of claim 70, wherein rate for the transmission channel exceeds rate for the conventional channel plus and exceeds rate for the robust channel ~~by an amount that varies depending on transmission robustness.~~

73. (currently amended) The method of claim ~~72~~ 62, further comprising:  
based at least in part upon updated rate of the data for the selected channel, identifying in the receiver a new buffer size parameter from among the multiple buffer size parameters of the multiple buffer models;

reconfiguring the buffer in the receiver according to the new buffer size parameter.

74. (previously presented) The method of claim 62, wherein the relatively higher level of robustness of the data of the robust channel is in terms of increased redundancy through channel coding techniques for the data of the robust channel.

75. (currently amended) The method of claim 62, wherein the relatively higher level of robustness of the data of the robust channel is in terms of increased use of cyclical redundancy codes or convolutional ~~block~~ codes within the data of the robust channel.

76. (previously presented) A computer-readable medium storing computer-executable instructions for causing the receiver programmed thereby to perform the method of claim 62.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: \_\_\_\_\_**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**